



January 2015

1. Identification

Name of the product: **ReadRight Antistatic ScreenKleen**

Product Identification Number(s): RR1261

Recommended use: Surface wipe

Use not recommended: Any use around the eyes or close to an ignition source.

Company: **Advantus Corporation**

**12276 San Jose Blvd., Ste. 618
Jacksonville, FL 32223**

Telephone: 904-482-0091

Fax number: 904-482-0099

Emergency: 1-800-327-1237

CHEMTREC (Transportation): 1-800-424-9300

CPR STATEMENT: This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is a greater potential for large-scale or prolonged exposure, in accordance with requirements of the U.S. Government's Occupational Safety and Health Administration (OSHA). It is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulation.

2. Hazard(s) identification

Emergency Overview

OSHA Hazards

Flammable liquid, Irritant

Other hazards which do not result in classification are: May form explosive peroxides.

GHS Classification

Flammable liquids (Cat. 2) H225 Highly flammable liquid and vapor.

Skin irritation (Cat. 3) H316 Causes mild skin irritation.

Eye irritation (Cat. 2A) H319 Causes serious eye irritation.

GHS Label elements, including precautionary statements

Pictogram:



Signal word: **Danger**

Hazard statements:

H225 Highly flammable liquid and vapor.

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ spray.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

3. Composition / Information on ingredients

Chemical identity:	2-Propanol	30%
Common name:	Isopropyl alcohol, Rubbing alcohol	
Numbers of identity:	CAS. 67-63-0	EINECS. 200-661-7
Chemical identity:	Alkyl Dimethyl Benzyl Ammonium Chloride	0.10%
Common name:	Benzalkonium chloride	
Numbers of identity:	CAS 68391-01-5	
Chemical identity:	Alkyl Dimethyl Ethyl Benzyl Ammonium Chloride	0.10%
Common name:	None	
Numbers of identity:	CAS 68956-79-6	
Chemical identity:	Ammonium hydroxide	0.05%
Common name:	Aqua Ammonia	
Numbers of identity:	CAS 7664-41-7	EINECS 215-697-6
Impurities:	None of toxicological significance.	

4. First-aid measures

P304+313 +341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a physician.

P302+352 IF ON SKIN: Wash with soap and water. Rinse until ammonia odor is gone.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes.
Remove contact lenses if present and easy to do; continue rinsing.

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed: Severe eye irritation. Skin irritation.

5. Firefighting measures

Suitable extinguishing equipment:

Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Emergency procedures:

Eliminate ignition source. Evacuate unnecessary personnel. Call appropriate fire fighting crew.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous decomposition products formed under fire conditions. - Carbon oxides, ammonia

Use water spray to cool unopened containers.

6. Accidental release measures

Use personal protective equipment. Avoid breathing, mist or vapors. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Be aware of possible accumulating vapors which could form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then absorb with industrial absorbent, or collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

See also Sec. 13.

7. Handling and storage

Precautions for safe handling:

Avoid contact with skin and eyes. Avoid inhalation of vapors or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking.

Prevent the build up of electrostatic charge.

Conditions for safe storage:

Keep container tightly closed in a dry and well-ventilated place.

Containers which have been opened must be resealed and kept upright to prevent leakage.

8. Exposure controls / personal protection

Information on the system design:

Product is intended for external use only. Stay up wind, out of any spray developed.

Exposure Limits:	Reference 29CFR 1910.1000 Table Z-1	
Component Name, CAS#	OSHA PEL	OSHA STEL
2-Propanol 67-63-0	400 ppm 980 mg/m ³	500 ppm 1,225 mg/m ³
	ACGIH TWA	ACGIH STEL
Ammonium hydroxide 7664-41-7	25 ppm	35 ppm as ammonia
Alkyl Dimethyl Benzyl Ammonium Chloride CAS 68391-01-5	NE	NE
Alkyl Dimethyl Ethyl Benzyl Ammonium Chloride		
NE= Not Established CAS 68956-79-6	NE	NE

Personal protective equipment

Respiratory protection: Where appropriate use a full-face supplied air respirator.
 Hand protection: Rubber gloves.
 Eye protection: Safety glasses with side-shields.
 Skin and body protection: Chemical resistant apron or protective suit if splashing or repeated contact with solution is likely; flame retardant and antistatic properties are recommended.

Hygiene measures

Wash hands and face before breaks and immediately after handling the product.
 Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance:	Clear, colorless liquid	
Odor:	Alcoholic ammonia	
Odor threshold:	The highest known value is 22 ppm (Isopropyl alcohol)	
pH-value:	Approx. 7-9	
Melting point:	no data available	
Freezing Point:	no data available	
Initial boiling point:	no data available	
Flash point:	22 °C (73 °F) - closed cup	
Evaporation rate:	no data available	
Flammability (solid, gas):	Not applicable	
Explosion limits:	Lower: 2% Upper: 12.7% (Isopropyl alcohol)	
Vapor pressure: (highest partial vapor pressure) at 20°C:	Not available	
Vapor density:	Not available	
Relative density (water=1.00):	no data available	Auto-ignition temperature: Not available
Solubility: Totally soluble in water at 20°C		Decomposition temperature: Not available
Partition coefficient: Log Kow =	Not applicable to mixture.	Viscosity: Like water

10. Stability and reactivity

Chemical stability: No decomposition, if used according to specifications.
 Possibility of hazardous reactions: May form explosive mixture with air.
 Conditions to avoid: Heat, flames and sparks. Extremes of temperature and direct sunlight.
 Materials to avoid: Aluminum, Acids, Oxidizing agents, Halogenated compounds, Acid anhydrides
 Hazardous decomposition products: Carbon oxides, product vapors.

11. Toxicological information

There is no data available for the product.

Routes of Entry: Absorbed through skin. Eye contact. Inhalation.

	2-Propanol
Oral Toxicity LD 50:	5143 mg/kg (Mouse) (Calculated value for 70% in water mixture)
Dermal Toxicity LD 50:	18286 mg/kg (Rabbit) (Calculated value for 70% in water mixture)
Inhalation Toxicity, Vapor, LC50	No data.
Eye Irritation (Rabbit)	No data.
Dermal Irritation (Rabbit)	No data.

Chronic Effects on Humans:

Carcinogenic effects: Classified A4 (Not classifiable for human or animal.) by ACGIH, (isopropyl alcohol)

Classified 3 (Not classifiable for human.) by IARC (Isopropyl alcohol).

Developmental toxicity: Classified Reproductive system/toxin/female.

Development toxin (Possible) (Isopropyl alcohol).

Contains material which may cause damage to the following organs: kidneys, liver, CNS,

Signs and Symptoms of Exposure:

Central nervous system depression, prolonged or repeated exposure can cause:, nausea, dizziness, narcosis, drowsiness,

12. Ecological information

Ecotoxicity: Not available for the product. BOD and COD: Not available.

Products of Biodegradation:

Hazardous short term degradation products are not likely.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

PBT and vPvB assessment: No data available.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Burn in a chemical incinerator equipped with an afterburner and scrubber.

Dispose in accordance with local, state and federal regulations.

14. Transport information

DOT (US)

UN3175 Solids containing flammable liquid, n.o.s., (Isopropanol), 4.1, 4.1, PG II

15. Regulatory information

OSHA Hazards: Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

SARA 302 Components: None

SARA 313 Components: Isopropanol CAS 67-63-0, Ammonium hydroxide CAS 7664-41-7

Inventory Status: All components are on TSCA, EINECS/ELINCS, AICS, and DSL.

Federal and State Regulations:

State Right to Know lists (RTK): 2-Propanol: FL, IL, MA, MN, NJ, PA, RI,

Ammonia, Water: MA, PA, NJ

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).

Material causing other toxic effects: None

California Prop. 65 Components: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Safety Data Sheet

16. Other information

SDS Preparation date:		November 25, 2014.		SDS Code:		AC CT812	
Hazard Categories:		Health	Fire	Pressure	Reactivity	Reference 49 CFR 171.8,	
Immediate	Yes	Yes	No	No	No	OSHA 29 CFR 1910.1200 and	
Delayed	Yes	No	XXX	XXX	XXX	SARA 302/311/312/313.	
HMIS Hazard ratings:		Health 1	Fire 3	Instability 0	Other B (Goggles, gloves)		
Hazard Ratings:		Least: 0	Slight: 1	Moderate: 2	High: 3	Extreme: 4	

HMIS® is a registered trade and service mark of the NPCA.

Note: The information in this SDS was obtained from current reputable and competent sources.

However, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. It is the user's responsibility to determine safe conditions for the use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is a greater potential for large-scale or prolonged exposure, in accordance with requirements of the U.S. Government's Occupational Safety and Health Administration (OSHA).