



January 2018

1. Identification

Name of the product: **RR1302 R/R INKAWAY-HAND CLEANING WIPE**

Recommended use: Surface wipe.

Use not recommended: Any use around the eyes or close to an ignition source.

Company: **Advantus Corporation**
12276 San Jose Blvd. Bldg. 618
Jacksonville, FL 32223

Telephone: 904-482-0091

Fax number: 904-482-0099

Product Information: 904-482-0091

Emergency: 1-800-327-1237

Emergency Number: Chemtrec 800-424-9300

CPR STATEMENT: This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

2. Hazard(s) identification

Emergency Overview

OSHA Hazards

Flammable liquid, Irritant

Other hazards which do not result in classification are: None.

GHS Classification

Flammable liquids (Cat. 3) H2265 Flammable liquid and vapor.

GHS Label elements, including precautionary statements

Pictogram:



Signal word: **Warning**

Hazard statements:

H226 Flammable liquid and vapor.

H316 Causes mild skin irritation.

H320 Causes eye irritation

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ spray.

P305 + P351 + P338

if present and ea: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

3. Composition / Information on ingredients

Chemical identity: Ethanol 15%

Common name: Ethyl alcohol

Numbers of identity: CAS 64-17-5 EC No. 200578-6

Chemical identity: Alkyl Dimethyl Benzyl Ammonium Chloride 0.21%

Common name: Benzalkonium chloride

Numbers of identity: CAS 68391-01-5

Chemical identity: Alkyl Dimethyl Ethyl Benzyl Ammonium Chloride 0.21%

Numbers of identity: CAS 68956-79-6

Impurities: None which influence toxicology or classification.

4. First-aid measures

P304+313 +341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a physician.

P302+352 IF ON SKIN: Wash with soap and water.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes.

Remove contact lenses if present and easy to do; continue rinsing.

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed: Severe eye irritation. Skin irritation.

5. Firefighting measures

Suitable extinguishing equipment:

Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Emergency procedures:

Eliminate ignition source. Evacuate unnecessary personnel. Call appropriate fire fighting crew.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous decomposition products formed under fire conditions. - Carbon oxides, nitrogen compounds

Use water spray to cool unopened containers.

6. Accidental release measures

Use personal protective equipment. Avoid breathing, mist or vapors. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Be aware of possible accumulating vapors which could form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then absorb with industrial absorbent, or collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

See also Sec. 13.

7. Handling and storage

Precautions for safe handling:

Avoid contact with skin and eyes. Avoid inhalation of vapors or mist.

Keep away from sources of ignition - No smoking.

Prevent the build up of electrostatic charge.

Conditions for safe storage:

Keep container tightly closed in a dry and well-ventilated place.

Containers which have been opened must be resealed and kept upright to prevent leakage.

8. Exposure controls / personal protection

Information on the system design:

Product is intended for external use only. Stay up wind, out of any spray developed.

Exposure Limits:

Reference 29CFR 1910.1000 Table Z-1

Component Name, CAS#

OSHA TWA

ACGIH TLV

Ethanol 64-17-5

1,000 ppm 1,900 mg/m3

1,000 ppm

Eye Irritation (Rabbit) Mild
Dermal Irritation (Rabbit) None

Chronic Effects on Humans:

No ingredient in this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC, ACGIH, NTP, or OSHA.

California Prop. 65 chemicals: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Signs and Symptoms of Exposure:

Central nervous system depression, prolonged or repeated exposure can cause nausea, dizziness, drowsiness, narcosis.

12. Ecological information

Ecotoxicity: Not available for the product. BOD and COD: Not available.

Products of Biodegradation:

Hazardous short term degradation products are not likely.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

PBT and vPvB assessment: No data available.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Burn in a chemical incinerator equipped with an afterburner and scrubber.

Dispose in accordance with local, state and federal regulations.

14. Transport information

DOT (US)

Ethanol (solution) UN number: 1170 Class: 3 Packing group: III

Marine pollutant: No Poison Inhalation Hazard: No

Domestic transport: Not classified as dangerous goods under transport regulations.

Sea transport (IMDG): Not classified as dangerous goods under transport regulations.

Air transport (IATA/CAO): Not classified as dangerous goods under transport regulations.

The description shown may not apply to all shipping situations. Consult 49CFR, OSHA or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name, labeling) and mode-specific or quantity-specific shipping requirements. Not Restricted as per IATA, Special Provisions A46.

15. Regulatory information

OSHA Hazards: Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

SARA 302 Components: None

SARA 311/312 Hazards

Fire hazard, chronic health hazard

SARA 313 Components: None

Inventory Status: All components are on TSCA, EINECS/ELINCS, AICS, and DSL.

Safety Data Sheet

Federal and State Regulations:

State Right to Know lists (RTK): Ethanol (CAS 64-17-5): MA, PA, NJ

Water (CAS 7732-18-5): MA, PA, NJ

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

WHMIS (Canada): CLASS B-3: Flammable liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

Material causing other toxic effects: None

California Prop. 65 Components: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. Other information

SDS Preparation date: January 29, 2018 replacing SDS dated: June 12, 2015.

Hazard Categories:	Health	Fire	Pressure	Reactivity	Reference
Immediate	Yes	Yes	No	No	49 CFR 171.8, OSHA 29 CFR 1910.1200 and SARA 302/311/312/313.
Delayed	No	No	XXX	XXX	
HMIS Hazard ratings: Health 1 Fire 2 Instability 0 Other B (Goggles, gloves)					
Hazard Ratings: Least: 0 Slight: 1 Moderate: 2 High: 3 Extreme: 4					

HMIS® is a registered trade and service mark of the NPCA.

Replacing SDS dated: December 30, 2014

Note: The information in this SDS was obtained from current reputable and competent sources.

However, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. It is the user's responsibility to determine safe conditions for the use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is a greater potential for large-scale or prolonged exposure, in accordance with requirements of the U.S. Government's Occupational Safety and Health Administration (OSHA).