



1. Identification

Name of the product: **Wet and Dry Bulk** SDS Code: BX0264 3 19
 Product Identification Number(s): BX0264 Reviewed and updated: March 4, 2019
 Recommended use: Surface wipe solution
 Use not recommended: Any use around eyes or close to ignition source
 Company: **Advantus Corporation** Telephone: 904-482-0091
12276 San Jose Blvd., Ste. 618 Fax number: 904-482-0099
Jacksonville, FL 32223 Emergency: 1-800-327-1237
 CHEMTREC (Transportation): 1-800-424-9300

CPR STATEMENT: This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR. This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is a greater potential for large-scale or prolonged exposure, in accordance with requirements of the U.S. Government's Occupational Safety and Health Administration (OSHA). It is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulation.

2. Hazard(s) identification

Emergency Overview

OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

Other hazards which do not result in classification are: May form explosive peroxides.

GHS Classification

Flammable liquids (Cat. 2) H225 Highly flammable liquid and vapor.

Skin irritation (Cat. 3) H316 Causes mild skin irritation.

Eye irritation (Cat. 2A) H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure (Cat. 3)

GHS Label elements, including precautionary statements

Pictogram:



Signal word: **Danger**

Hazard statements:

H225 Highly flammable liquid and vapor.

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ s/ spray.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

3. Composition / Information on ingredients

Product is distributed as a single use, presaturated pad in which all the liquid is absorbed into the pad.

Chemical identity: 2-Propanol (solution) 30%

Common name: Isopropyl alcohol, Rubbing alcohol

Numbers of identity: CAS. 67-63-0 EINECS. 200-661-7

Chemical identity: Alkyl Dimethyl Benzyl Ammonium Chloride 0.1%

Common name: Benzalkonium chloride

Numbers of identity: CAS 68391-01-5

Impurities: None of toxicological significance.

4. First-aid measures

P304+313 +341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a physician.
 P302+352 IF ON SKIN: Wash with soap and water. Rinse until ammonia odor is gone.
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes.
 Remove contact lenses if present and easy to do; continue rinsing.
 P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 Most important symptoms and effects, both acute and delayed: Severe eye irritation. Skin irritation.

5. Firefighting measures

Suitable extinguishing equipment:

Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Emergency procedures:

Eliminate ignition source. Evacuate unnecessary personnel. Call appropriate fire fighting crew.
 Special protective equipment for firefighters
 Wear self contained breathing apparatus for fire fighting if necessary.
 Hazardous decomposition products formed under fire conditions. - Carbon oxides, ammonia
 Use water spray to cool unopened containers.

6. Accidental release measures

Use personal protective equipment. Avoid breathing, mist or vapors. Ensure adequate ventilation.
 Remove all sources of ignition. Evacuate personnel to safe areas. Be aware of possible accumulating vapors which could form explosive concentrations. Vapors can accumulate in low areas.
 Environmental precautions:
 Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
 Methods and materials for containment and cleaning up
 Contain spillage, and then absorb with industrial absorbent, or collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.
 See also Sec. 13.

7. Handling and storage

Precautions for safe handling:

Avoid contact with skin and eyes. Avoid inhalation of vapors or mist.
 Use explosion-proof equipment. Keep away from sources of ignition - No smoking.
 Prevent the build up of electrostatic charge.

Conditions for safe storage:

Keep container tightly closed in a dry and well-ventilated place.
 Containers which have been opened must be resealed and kept upright to prevent leakage.

8. Exposure controls / personal protection

Information on the system design:

Product is intended for external use only. Stay up wind, out of any spray developed.

Exposure Limits:	Reference 29CFR 1910.1000 Table Z-1	
Component Name, CAS#	OSHA PEL	OSHA STEL
2-Propanol 67-63-0	400 ppm 980 mg/m ³	500 ppm 1,225 mg/m ³
	ACGIH TWA	ACGIH STEL
Ammonium hydroxide 7664-41-7	25 ppm	35 ppm as ammonia
Alkyl Dimethyl Benzyl Ammonium Chloride CAS 68391-01-5	NE	NE

NE= Not Established

Personal protective equipment

Respiratory protection: Where appropriate use a full-face supplied air respirator.
 Hand protection: Rubber gloves.
 Eye protection: Safety glasses with side-shields.
 Skin and body protection: Chemical resistant apron or protective suit if splashing or repeated contact with solution is likely; flame retardant and antistatic properties are recommended.

Hygiene measures

Wash hands and face before breaks and immediately after handling the product.
 Handle in accordance with good industrial hygiene and safety practice.

14. Transport information

DOT (US) Special precautions for local transport or conveyance: None

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol (Solution)

Reportable Quantity (RQ): Not applicable

Marine pollutant: No

IMDG

UN number: 1219 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: Isopropanol (Solution)

Marine pollutant: No

IATA

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol

15. Regulatory information

OSHA Hazards: Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

SARA 302 Components: None

SARA 313 Components: Isopropanol CAS 67-63-0, Ammonium hydroxide CAS 7664-41-7

Inventory Status: All components are on TSCA, EINECS/ELINCS, AICS, and DSL.

Federal and State Regulations:

State Right to Know lists (RTK): 2-Propanol: FL, IL, MA, MN, NJ, PA, RI,
Ammonia, Water: Ma, PA, NJ

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B:

CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B:

Material causing other toxic effects: None

California Prop 65: This product will not expose you to chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

16. Other information

SDS Preparation date: November 13, 2014. SDS Code: AC BX0264 3 19

Hazard Categories:	Health	Fire	Pressure	Reactivity	Reference 49 CFR 171.8,
Immediate	Yes	Yes	No	No	OSHA 29 CFR 1910.1200 and SARA 302/311/312/313.
Delayed	Yes	No	XXX	XXX	
HMIS Hazard ratings: Health 2 Fire 3 Instability 0 Other B (Goggles, gloves)					
Hazard Ratings: Least: 0 Slight: 1 Moderate: 2 High: 3 Extreme: 4					

HMIS® is a registered trade and service mark of the NPCA.

Note: The information in this SDS was obtained from current reputable and competent sources.

However, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. It is the user's responsibility to determine safe conditions for the use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.