



### 1. Identification

Name of the product: **TEXSOLVE** SDS Code: CT 135 3 19  
 Product Identification Number(s): CT135 SDS reviewed and updated: March 4, 2019  
 Recommended use: Spray cleaner  
 Use not recommended: Any use contacting skin or subject to inhaling large amount of fumes, or exposure to flame.  
 Company: **Advantus Corporation** Telephone: 904-482-0091  
**12276 San Jose Blvd., Ste. 618** Fax number: 904-482-0099  
**Jacksonville, FL 32223** Emergency: 1-800-327-1237  
 CHEMTREC (Transportation): 1-800-424-9300

CPR STATEMENT: This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR. This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is a greater potential for large-scale or prolonged exposure, in accordance with requirements of the U.S. Government's Occupational Safety and Health Administration (OSHA). It is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulation.

### 2. Hazards identification

#### Emergency Overview

#### GHS Classification

OSHA Hazards per 29 CFR 1910: OSHA HCS

Combustible Liquid, Irritant

GHS Classification

Flammable liquids (Category 4)	H227 Combustible liquid
Acute toxicity, Oral (Category 5)	H303 May be harmful if swallowed.
Skin irritation (Category 2)	H315 Causes skin irritation.
Aspiration hazard (Category 1)	H304 May be fatal if swallowed and enters airways.
Chronic aquatic toxicity (Category 2)	H411 Toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification are: None

GHS Label elements, including precautionary statements

Pictogram:



Signal word: Danger

#### Hazard statements:

H227 Combustible liquid  
 H303 May be harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements:

P273 Avoid release to the environment.  
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
 P331 Do NOT induce vomiting.

### 3. Composition / Information on ingredients

Chemical identity: Petroleum distillate 98.75%  
 Common name: Kerosene  
 Numbers of identity: CAS 8008-20-6/ 64742-47-8  
 Impurities: None which contributes to the classification of the product.

## 4. First-aid measures

P304+313 +341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a physician.  
 P302+352 IF ON SKIN: Wash with soap and water.  
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes.  
 Remove contact lenses if present and easy to do; continue rinsing.  
 P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 Most important symptoms and effects, both acute and delayed: Eye irritation. Skin irritation.

## 5. Firefighting measures

**Suitable extinguishing equipment:**

Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**Emergency procedures:**

Special protective equipment for firefighters consists of:

Self contained breathing apparatus for fire fighting if necessary.

Hazardous decomposition products are formed under fire conditions and the nature of the decomposition products is not known.

Extinguishing Media: Water Spray, Water fog, Dry Chemical, Carbon dioxide. "Alcohol" foam.

## 6. Accidental release measures

Use personal protective equipment. Avoid breathing, mist or vapors. Ensure adequate ventilation.  
 Remove all sources of ignition. Beware of vapors accumulating to form explosive concentrations.  
 Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.  
 Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations. Keep in suitable, closed containers for disposal.  
 If this product is spilled and not recovered, or is recovered as a waste for treatment or disposal, the CERCLA Reportable Quantity is 100 lbs. (Release of an unlisted Hazardous Waste characteristic of ignitability).

## 7. Handling and storage

**Precautions for safe handling:**

Avoid contact with skin and eyes. Avoid inhalation of vapors or mist. No smoking.  
 Keep away from sources of ignition. Take measures to prevent the build up of electrostatic charge.  
 Use only with adequate ventilation. Avoid repeated or prolonged contact with skin or eyes.  
 Wash thoroughly after handling.

**Conditions for safe storage:**

Do not store in direct sunlight.  
 Store in cool dry place, away from heat, sparks or flames which may generate toxic decomposition products.  
 Vapors are heavy and may concentrate in low poorly ventilated areas.

## 8. Exposure controls / personal protection

Information on the system design:

Product is intended for external use only. Stay up wind, out of any spray developed.

	Exposure Limits:	NIOSH TWA	ACGIH TLV (ppm)
Kerosene	CAS 8008-20-6/ 64742-47-8	100 mg/m <sup>3</sup>	200 mg/m <sup>3</sup>

Precautions:

Central Nervous System impairment, Upper Respiratory Tract irritation, Skin irritation  
 Application restricted to conditions in which there are negligible aerosol exposures  
 Confirmed animal carcinogen with unknown relevance to humans.

**Personal protective equipment**

Product is a liquid which forms vapors heavier than air. Avoid breathing vapors.  
 Protect skin from liquid.

**Engineering Controls:** Do not use near any spark-producing electrical devices.

**Respiratory Protection:** Use only with adequate ventilation. Keep container closed. Use approved NIOSH self-contained or supplied air respirators for emergencies and in situations where air may be displaced by vapors.

**Eye Protection:** Use chemical protective safety glasses.

**Hygiene measures:**

Wash hands and face before breaks and immediately after handling the product.  
 Handle in accordance with good industrial hygiene and safety practice.

Protective Clothing:

Where there is potential for skin contact, use appropriate impervious gloves, apron, pants and jacket.



**14. Transport information**

DOT CLASSIFICATION: Special precautions for local transport or conveyance: None  
 Proper Shipping Name: Consumer Commodity  
 Hazard Class: ORM-D  
 UN Number: Does not apply  
 Packing Group: Does not apply  
 Hazard Labeling: ORM, ORM-D-Air  
 IATA/ICAO CLASSIFICATION:  
 Proper Shipping Name: Consumer Commodity  
 Hazard Class: Class 9, Miscellaneous  
 UN Number: ID#8000  
 Packing Group: Does not apply  
 Hazard Labeling: Class 9, Miscellaneous

The description shown may not apply to all shipping situations. Consult 49CFR, OSHA or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name, labeling) and mode-specific or quantity-specific shipping requirements,

**15. Regulatory information**

SARA 302: None subject to the reporting requirements of SARA Title III, Section 302.  
 SARA Title III, Section 313: See below  
 SARA 311/312 Hazards  
 Acute : Yes` Chronic : Yes Fire : Yes Reactivity : No Pressure : No  
 TSCA Inventory Status: All components are listed in the TSCA inventory.  
 Product has the characteristic of flammability and qualifies as "Unlisted Hazardous Waste D001" RQ 100#.

**California Prop. 65 Components**



WARNING::This product can expose you to chemicals including kerosene which is known to the state of California to cause cancer, birth defects or other reproductive harm.

For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

State Right-to-Know Regulations Status of Ingredients: MA PA NJ Prop. 65 SARA 313, dm  
 Kerosene CAS 8008-20-6/ 64742-47-8 Yes Yes Yes No No

**16. Other information**

SDS Preparation date: December 22, 2014 SDS Code: AC CT135 3 19

Hazard Categories:	Health	Fire	Pressure	Reactivity	Reference 49 CFR 171.8,
Immediate	Yes	Yes	No	No	OSHA 29 CFR 1910.1200 and
Delayed	No	No	XXX	XXX	SARA 302/311/312/313.
HMIS Hazard ratings: Health 2 Fire 2 Instability 0 Other B (Goggles, gloves)					
Hazard Ratings: Least: 0 Slight: 1 Moderate: 2 High: 3 Extreme: 4					

HMIS® is a registered trade and service mark of the NPCA.

Note: The information in this SDS was obtained from current reputable and competent sources. However, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. It is the user's responsibility to determine safe conditions for the use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product. This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is a greater potential for large-scale or prolonged exposure, in accordance with requirements of the U.S. Government's Occupational Safety and Health Administration (OSHA).